

25ppm, 0.1%, ESD Tolerant High Precision Resistors



RS73 – Series

KOA's new RS73-series are ESD transient tolerant high precision and high reliability resistors using thick film technology.

With a T.C.R. down to 25ppm and a tolerance as low as 0.1%, the new RS73-series from KOA is ideal for precision designs such as high-accuracy sensing or voltage detection circuits in automotive, industrial and measuring applications, where ESD sensitivity is an issue.

The new RS73-series also features an **excellent long term stability**.

Currently, the RS73 series is only available in 0603 size.

However, 0805 and 1206 are under development and will be released soon.



Features

- $\pm 0.1\%$, $\pm 0.25\%$, $\pm 0.5\%$, $\pm 1\%$ tolerances available
- $\pm 25\text{ppm/K}$, $\pm 50\text{ppm/K}$
- $\pm 0.2\%$ ~ Long term stability
- ESD stability of thick film resistors
- Ideal for applications where thin film is not suitable
- Anti-Sulfuration type also available (RS73-RT)
- EU-RoHS compliant, AEC-Q200 qualified

Application Examples

- High precision circuits for automotive and industrial
- Motor controls
- AC adapters
- A/D signal conversion
- Switching boards
- Industrial equipment & measurement

Ratings

Type	Size (inch)	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R. (ppm/K)	Resistance Range (E24 & E96)*2				Max. Working Voltage	Max. Overload Voltage
						B: $\pm 0.1\%$	C: $\pm 0.25\%$	D: $\pm 0.5\%$	F: $\pm 1\%$		
RS73F1J	0603	0.125 W	+70 °C	+125 °C	$\pm 25^{*1}$	100 Ω ~ 1 M Ω				75 V	150V
RS73G1J					± 50						

*1 Cold T.C.R. (-55°C/+25°C) is -50/~ +25 ppm/K

*2 Please contact KOA in case E192 values are needed

Operating Temperature Range: -55 °C ... +155 °C

Performance

Parameter	Test method	Limit ΔR		Typical ΔR	
		100 Ω ≤R≤200k Ω	200k Ω <R≤1M Ω	100 Ω ≤R≤200k Ω	200k Ω <R≤1M Ω
Short Time Overload	Rated voltage x 2.5 for 5sec (Not exceeding max. overload voltage)	$\pm 0.2\%$		$\pm 0.03\%$	
Resistance to soldering heat	+260°C $\pm 5^\circ\text{C}$, 10sec $\pm 1\text{sec}$			$\pm 0.1\%$	
Rapid change of temperature	-55°C(30min.) / +125°C(30min.), 1000cycles			$\pm 0.05\%$	
High Temperature exposure	+155°C $\pm 3^\circ\text{C}$, 1000hrs	$\pm 0.2\%$	$\pm 0.4\%$	$\pm 0.1\%$	$\pm 0.2\%$
Moisture resistance	+40°C $\pm 2^\circ$, 90~95%RH, 1000hrs 1.5h ON / 0.5h OFF cycle	$\pm 0.2\%$	$\pm 0.4\%$	$\pm 0.04\%$	$\pm 0.08\%$
Rated load / Endurance	+70°C $\pm 2^\circ$, 1000hrs, 1.5h ON/0.5h OFF cycle	$\pm 0.2\%$		$\pm 0.05\%$	



For more information, please contact:

KOA Europe GmbH, Kaddenbusch 6, D-25578 Dägeling-Itzehoe, Germany

Phone: +49 (0)4821 89890, E-Mail: info@koaeurope.de, Internet: www.koaeurope.de