AEC-Q200 qualified, ±0.5 %, ±50 ppm/K, High Precision, Anti-Pulse Resistor



KOAs new SG73G-series thick film resistors are designed for applications where high precision and pulse stability are essential.

The new SG73G-series has a T.C.R. of ± 50 ppm/K as well as a tolerance of ± 0.5 % so it is ideal for precision designs such as high-accuracy sensing or voltage detection circuits in automotive and industrial applications. The special inner construction offers also an outstanding pulse load capability and allows higher rated power.



Features:

- Outstanding pulse proof properties
- High precision: ±0.5 %, T.C.R. ±50 ppm/K
- High power rating
- 30 Ω to 1 M Ω
- Available in 0603, 0805 and 1206
- Improved high temperature reliability (-55 °C to +155 °C)
- AEC-Q200 qualified


Application Examples:

- Automotive electronics (e.g. ECU)
- Power supplies
- Industrial Electronics
- Measuring instruments
- Motor controls
- Smart meters
- Power conditioners / inverters
- White goods

Ratings:

Туре	Size (inch)	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R.	Resistance Range E24 & E96 D: ±0.5 %	Max. Working Voltage	Max. Overload Voltage
SG73G1J	0603	0.2 W	+70 °C	+125 °C	±50 ppm/K	30 Ω - 1 ΜΩ	150 V	200 V
		0.33 W*	ı	+125 °C				
SG73G2A	0805	0.25 W	+70 °C	+125 ℃			200 V	400 V
		0.5 W*	-	+100 °C			200 V	400 0
SG73G2B	1206	0.33 W	+70 °C	+125 ℃			200 V	400 V
		0.5 W*	-	+120 °C				

^{*}Increased power ratings are allowed acc. to derating curve based on terminal part temperature.



One-Pulse Limiting Electric Power

For more information, please contact:

KOA Europe GmbH, Kaddenbusch 6, D-25578 Dägeling-Itzehoe, Germany

Phone: +49 (0)4821 89890, E-Mail: koa-europe@koaeurope.de, Internet: www.koaeurope.de